



# Product Data Sheet

## Eastman Solus™ 2100 Performance Additive

### Application/Uses

- Industrial 2K coatings, for example automotive refinish

### Key Attributes

- Ease of sanding
- Excellent anti-sag behavior
- Faster dry to touch time
- Improved gloss
- Wider window of polishability

### Product Description

Eastman Solus™ 2100 Performance Additive is a dry, free-flowing powder convenient to handle. It is soluble in a wide range of solvents and compatible in most high solids coatings systems.

### Typical Properties

Property	Typical Value, Units
Appearance	Free-flowing white powder
Solids	100%
Bulk factor, poured lb/ft <sup>3</sup>	31-39 (0.49-0.62 kg/L)
Polymer Density (lbs/gal)	9.89 (1.2 kg/L)
Hydroxyl Content	1.2-1.9 wt %
Tg	70-80°C

### Comments

Properties reported here are typical of average lots. Eastman makes no representation that the material in any particular shipment will conform exactly to the values given.

### Packaging

20 Kg drums lined with polyethylene bag

### Storage

Keep container closed

*Eastman and its marketing affiliates shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability of fitness of any product, and nothing herein waives any of the Seller's conditions of sale.*